

Product Technical Sheet

12 Aug 2021 10:00



659.SK5141-02

PILLAR SMART-K - OPTIMA

4 NR IP56 340x810x260mm

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Protection degree	Splash proof	IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations
Mounting version	ON TURRET		
Type of product	PILLAR SMART-K - OPTIMA	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Commercial series	KIOSK Series		
Synthetical description	PILLAR SMART-K - OPTIMA	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
Material	THERMOPLASTIC		
Dimensions	340x810x260mm		
Protection degree IP	IP56		
Protection degree IK	IK10		
Inlet supply unit	Supply by terminal block		
No. of available outlets	4 NR		
No. of sockets 2P+E 16A	4 NR		
In disp. ing/tipo apparecchio	Disconnecting switch 4P 40A		
No. RCBO 2P 6A 0,03A	4 NR		