

## Product Technical Sheet

12 Aug 2021 10:01



# 659.SK5163-06

## PILLAR SMART-K - OPTIMA

6 NR IP56 340x810x260mm

Product Approvals

| TECHDATA                      |                             | STANDARDS AND LAWS                |  |
|-------------------------------|-----------------------------|-----------------------------------|--|
| Protection degree             | Splash proof                | IEC 61439-7 (2018)                | [International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations |
| Mounting version              | ON TURRET                   |                                   |  |
| Commercial series             | KIOSK Series                |                                   |  |
| Type of product               | PILLAR SMART-K - OPTIMA     | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive  |
| Synthetical description       | PILLAR SMART-K - OPTIMA     | DIRECTIVE EMC 2014/30/UE          | [European Directives] Electromagnetic Compatibility Directive  |
| Material                      | THERMOPLASTIC               |                                   |  |
| Dimensions                    | 340x810x260mm               |                                   |  |
| Protection degree IP          | IP56                        |                                   |  |
| Protection degree IK          | IK10                        |                                   |  |
| Inlet supply unit             | Supply by terminal block    |                                   |  |
| No. of available outlets      | 6 NR                        |                                   |  |
| No. of sockets 2P+E 16A       | 6 NR                        |                                   |  |
| N ° KIT Water                 | 2 NR                        |                                   |  |
| In disp. ing/tipo apparecchio | Disconnecting switch 4P 40A |                                   |  |
| No. RCBO 2P 6A 0,03A          | 6 NR                        |                                   |  |