

## Product Technical Sheet

12 Aug 2021 10:11



# 749.5005-351

## INDUSTRIAL CABLE REEL

IP44 16A 3P+E 400V 50m

Product Approvals

| TECHDATA                 |                       | STANDARDS AND LAWS                |   |
|--------------------------|-----------------------|-----------------------------------|---|
| Protection degree        | Splash proof          | EN 61316 (1999)                   | [European Standard] Industrial cable reels  |
| Commercial series        | ROLLER 450 Series     | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Type of product          | INDUSTRIAL CABLE REEL |                                   |   |
| Synthetical description  | INDUSTRIAL CABLE REEL |                                   |   |
| Protection degree IP     | IP44                  |                                   |   |
| Inlet supply unit        | Plug IEC 309 3P+E 16A |                                   |   |
| No. of available outlets | 1 NR                  |                                   |   |
| No. of sockets 3P+E 16A  | 1 NR                  |                                   |   |
| Rated current            | 16A                   |                                   |   |
| Poles                    | 3P+E                  |                                   |   |
| Rated voltage            | 400V                  |                                   |   |
| Cable length             | 50m                   |                                   |   |
| Cable section            | 2,5mm <sup>2</sup>    |                                   |   |
| Wound cable power        | 4000W                 |                                   |   |
| Unwound cable power      | 11000W                |                                   |   |
| Material                 | ENGINEERING PLASTIC   |                                   |   |
| Protection degree IK     | IK08                  |                                   |   |
| Options                  | With wheels stand     |                                   |   |

Options

With disconnecter