

Product Technical Sheet

12 Aug 2021 10:14



219.125366.RU

PLUG

125A 3P+E 7h 480-500V 50Hz 60Hz II 2GD
Screw terminals EAC [Eurasian Conformity]



Product Approvals

TECHDATA

| | |
|----------------------------|----------------------|
| Commercial series | OPTIMA-EX[GD] Series |
| Type of product | PLUG |
| Synthetical description | PLUG |
| Mounting version | PORTABLE |
| Rated current | 125A |
| Poles | 3P+E |
| Hour position | 7h |
| Rated voltage (range) | 400-up |
| Rated voltage | 480-500V |
| Working frequency | 50Hz |
| Working frequency | 60Hz |
| Colour | BLACK |
| Material | THERMOPLASTIC |
| Protection degree | Splash proof |
| Protection degree IP | IP66 |
| Types of available outlets | STRAIGHT |
| Terminals | Screw terminals |
| Contact material | CuZn (brass) |
| | |

| | |
|----------------------------|---------------------------|
| Surface treatment contacts | Nickel-plated |
| Cable entry | CABLE GLAND |
| Group and categories EX | II 2GD |
| Ambient temperature Ta min | -35 °C |
| Ambient temperature Ta max | 60 °C |
| Options | EAC [Eurasian Conformity] |