

Product Technical Sheet

12 Aug 2021 10:15



219.16334.RU

PLUG

16A 2P+E 3h >50-250V DC II 2GD Screw terminals EAC [Eurasian Conformity] Low temperature [-50°C]



Product Approvals

TECHDATA

| | |
|----------------------------|----------------------|
| Type of product | PLUG |
| Commercial series | OPTIMA-EX[GD] Series |
| Synthetical description | PLUG |
| Mounting version | PORTABLE |
| Rated current | 16A |
| Poles | 2P+E |
| Hour position | 3h |
| Rated voltage (range) | 50-200V |
| Rated voltage | >50-250V |
| Working frequency | DC |
| Colour | RED |
| Material | THERMOPLASTIC |
| Protection degree | Splash proof |
| Protection degree IP | IP66 |
| Types of available outlets | STRAIGHT |
| Terminals | Screw terminals |
| Contact material | CuZn (brass) |
| Surface treatment contacts | Nickel-plated |

| | |
|----------------------------|---------------------------|
| Cable entry | CABLE GLAND |
| Group and categories EX | II 2GD |
| Ambient temperature Ta min | -50 °C |
| Ambient temperature Ta max | 60 °C |
| Options | Low temperature [-50°C] |
| Options | EAC [Eurasian Conformity] |