

Product Technical Sheet

12 Aug 2021 10:22



504.1670.RU

INTERLOCKED SOCKET

16A 2P+E 4h 100-130V 50Hz 60Hz II 2GD
130X260MM_PAR Screw terminals With
mechanical interlock EAC [Eurasian Conformity]

Product Approvals

TECHDATA

Commercial series	ADVANCE-GRP[GD] Series
Type of product	INTERLOCKED SOCKET
Synthetical description	INTERLOCKED SOCKET
Mounting version	SURFACE MOUNTING
Rated current	16A
Poles	2P+E
Hour position	4h
Rated voltage (range)	50-200V
Rated voltage	100-130V
Working frequency	60Hz
Working frequency	50Hz
Colour	YELLOW
Material	GRP Glass Reinforced Polyester
Protection degree	Splash proof
Protection degree IP	IP66
Protection degree IK	IK10
Terminals	Screw terminals
Contact material	CuZn (brass)

Flange	130X260MM_PAR
Cable entry	1xM25
Working temperature	-40°C/+60°C
GLOW WIRE	GW 960°C
Self-extinguishing UL94	V0
Group and categories EX	II 2GD
Ambient temperature Ta min	-35 °C
Ambient temperature Ta max	60 °C
Options	With mechanical interlock
Options	EAC [Eurasian Conformity]
Padlock	ø5mm