



## 504.1683-A.RU

### INTERLOCKED SOCKET

16A 2P+E 6h 200-250V 50Hz 60Hz II 2GD  
 130X260MM\_PAR Screw terminals With  
 mechanical interlock EAC [Eurasian Conformity]  
 Low temperature [-50°C]

Product Approvals

| TECHDATA                |                                   | STANDARDS AND LAWS           |   |
|-------------------------|-----------------------------------|------------------------------|---|
| Commercial series       | ADVANCE-GRP[GD] Series            | DIRECTIVE ATEX<br>2014/34/UE | [European Directives] Atmosphere<br>Explosive |
| Type of product         | INTERLOCKED SOCKET                |                              |   |
| Synthetical description | INTERLOCKED SOCKET                |                              |   |
| Mounting version        | SURFACE MOUNTING                  |                              |   |
| Rated current           | 16A                               |                              |   |
| Poles                   | 2P+E                              |                              |   |
| Hour position           | 6h                                |                              |   |
| Rated voltage (range)   | 200-250V                          |                              |   |
| Rated voltage           | 200-250V                          |                              |   |
| Working frequency       | 60Hz                              |                              |   |
| Working frequency       | 50Hz                              |                              |   |
| Colour                  | BLUE                              |                              |   |
| Material                | GRP Glass Reinforced<br>Polyester |                              |   |
| Protection degree       | Splash proof                      |                              |   |
| Protection degree IP    | IP66                              |                              |   |
| Protection degree IK    | IK10                              |                              |   |
| Terminals               | Screw terminals                   |                              |   |
| Contact material        | CuZn (brass)                      |                              |   |

|                            |                           |
|----------------------------|---------------------------|
| Flange                     | 130X260MM_PAR             |
| Cable entry                | 1xM25                     |
| Working temperature        | -40°C/+60°C               |
| GLOW WIRE                  | GW 960°C                  |
| Self-extinguishing UL94    | V0                        |
| Group and categories EX    | II 2GD                    |
| Ambient temperature Ta min | -50 °C                    |
| Ambient temperature Ta max | 60 °C                     |
| Options                    | With mechanical interlock |
| Options                    | EAC [Eurasian Conformity] |
| Options                    | Low temperature [-50°C]   |
| Padlock                    | ø5mm                      |