



504.63867.RU

INTERLOCKED SOCKET

63A 3P+E 5h 600-690V 50Hz 60Hz II 2GD
170X380MM_PAR Screw terminals With
mechanical interlock EAC [Eurasian Conformity]

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|--------------------------------|----------------------|---|
| Commercial series | ADVANCE-GRP[GD] Series | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Type of product | INTERLOCKED SOCKET | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description | INTERLOCKED SOCKET | | |
| Mounting version | SURFACE MOUNTING | | |
| Rated current | 63A | EN 60309-1/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Poles | 3P+E | EN 60309-2/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Hour position | 5h | | |
| Rated voltage (range) | 400-up | EN 60079-7 (2007) | [European Standard] Explosive atmospheres. Equipment protection by increased safety "e" |
| Rated voltage | 600-690V | | |
| Working frequency | 60Hz | EN 60309-4 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock |
| Working frequency | 50Hz | | |
| Colour | RED | EN 60079-0 (2009) | [European Standard] Explosive atmospheres. General requirements. |
| Material | GRP Glass Reinforced Polyester | EN 60079-31 (2009) | [European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t" |
| Protection degree | Splash proof | EN 60079-1 (2007) | [European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures "d" |
| Protection degree IP | IP66 | EN 60309-1/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Protection degree IK | IK10 | | |
| Terminals | Screw terminals | EN 60309-2/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Contact material | CuZn (brass) | | |

| | | | |
|----------------------------|---------------------------|------------------------------|---|
| Flange | 170X380MM_PAR | EN 60309-4/A1 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock |
| Cable entry | 1xM40 | | |
| Working temperature | -40°C/+60°C | DIRECTIVE ATEX 2014/34/UE | [European Directives] Atmosphere Explosive |
| GLOW WIRE | GW 960°C | | |
| Self-extinguishing UL94 | V0 | | |
| Group and categories EX | II 2GD | | |
| Ambient temperature Ta min | -35 °C | | |
| Ambient temperature Ta max | 60 °C | | |
| Options | With mechanical interlock | | |
| Options | EAC [Eurasian Conformity] | | |
| Padlock | ø6,3mm | | |