

## Product Technical Sheet

12 Aug 2021 10:30



# 504.6387.RU

## INTERLOCKED SOCKET

63A 3P+N+E 6h 346-415V 50Hz 60Hz II 2GD  
170X380MM\_PAR Screw terminals With  
mechanical interlock EAC [Eurasian Conformity]

Product Approvals

### TECHDATA

Commercial series	ADVANCE-GRP[GD] Series
Type of product	INTERLOCKED SOCKET
Synthetical description	INTERLOCKED SOCKET
Mounting version	SURFACE MOUNTING
Rated current	63A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	50Hz
Working frequency	60Hz
Colour	RED
Material	GRP Glass Reinforced Polyester
Protection degree	Splash proof
Protection degree IP	IP66
Protection degree IK	IK10
Terminals	Screw terminals
Contact material	CuZn (brass)

Flange	170X380MM_PAR
Cable entry	1xM40
Working temperature	-40°C/+60°C
GLOW WIRE	GW 960°C
Self-extinguishing UL94	V0
Group and categories EX	II 2GD
Ambient temperature Ta min	-35 °C
Ambient temperature Ta max	60 °C
Options	With mechanical interlock
Options	EAC [Eurasian Conformity]
Padlock	ø6,3mm