



644.0345-LDB

SURFACE MOUNTING BOX

122x120x90mm IP66 LED LIGHT 12-250VAC /VDC BLUE THERMOSETTING

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Type of product	SURFACE MOUNTING BOX	EN 60079-31 (2014)	[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"
Commercial series	ZENITH-P Series	EN 60079-1 (2014)	[European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures 'd'
Synthetical description	SURFACE MOUNTING BOX	EN 60079-7 (2015)	[European Standard] Explosive atmospheres. Equipment protection by increased safety "e"
Protection degree	Splash proof	EN 60079-0 (2018)	[European Standard] Explosive atmospheres. General requirements.
Protection degree IP	IP66	DIRECTIVE ATEX 2014/34/UE	[European Directives] Atmosphere Explosive
Material	THERMOSETTING		
Equipment	Control station		
Function	LED LIGHT 12-250VAC/VDC		
Colour	BLUE		
Dimensions	122x120x90mm		
Cable entry	1xM20		
Rated current (value)	10 mA		
Category of use	AC12		
Rated Sizing Voltage (Value)	250 V		
Maximum power dissipation	1,230 W		
Group and categories EX	II 2GD		
Modo protezione gas	Ex db eb IIC T6 Gb		
Dust protection	Ex tb IIIC T80°C Db IP66		

Ambient temperature Ta min	-30 °C
Ambient temperature Ta max	40 °C