



644.0345-LDW

SURFACE MOUNTING BOX

122x120x90mm IP66 LED LIGHT 12-250VAC /VDC WHITE THERMOSETTING

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	ZENITH-P Series	EN 60079-31 (2014)	[European Standard] Explosive atmospheres. Equipment dust ignition protection by enclosure "t"
Type of product	SURFACE MOUNTING BOX	IEC 60079-31 (2013)	[International Standard] Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
Synthetical description	SURFACE MOUNTING BOX	EN 60079-1 (2014)	[European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures 'd'
Protection degree	Splash proof	EN 60079-7 (2015)	[European Standard] Explosive atmospheres. Equipment protection by increased safety "e"
Protection degree IP	IP66	IEC 60079-1 (2014)	[International Standard] Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d".
Material	THERMOSETTING	IEC 60079-7 (2015)	[International Standard] Explosive atmospheres - Part 7: Equipment protection by increased safety "e".
Equipment	Control station	IEC 60079-0 (2017)	[International Standard] Explosive atmospheres - Part 0: Equipment - General requirements
Function	LED LIGHT 12-250VAC/VDC	EN 60079-0 (2018)	[European Standard] Explosive atmospheres. General requirements.
Colour	WHITE	DIRECTIVE ATEX 2014/34/UE	[European Directives] Atmosphere Explosive
Dimensions	122x120x90mm		
Cable entry	1xM20		
Rated current (value)	10 mA		
Category of use	AC12		
Rated Sizing Voltage (Value)	250 V		
Maximum power dissipation	1,230 W		
Group and categories EX	II 2GD		
Modo protezione gas	Ex db eb IIC T6 Gb		
Dust protection	Ex tb IIIC T80°C Db IP66		

Ambient temperature Ta min	-30 °C
Ambient temperature Ta max	40 °C