



204.WD21B-T23A

WALL BOX 2 SOCKETS WITH LOCK

Type 2 3P+N+E 32A 400V~ 22kW Type 3A
1P+N+E 16A 230V~ 3,7kW 32A 400V 3P+N+E
IP54 IK10

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|--------------------------------|-----------------------------------|--|
| Commercial series | LIBERA Series | IEC 61439-7 (2018) | [International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations |
| Type of product | WALL BOX 2 SOCKETS WITH LOCK | | |
| Synthetical description | WALL BOX 2 SOCKETS WITH LOCK | EN IEC 61851-1 (2019) | [European Standard] Electric vehicle conductive charging system - Part 1: General requirements |
| Material | ENGINEERING PLASTIC | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| EV standard | Type 3A 1P+N+E 16A 230V~ 3,7kW | DIRECTIVE EMC 2014/30/UE | [European Directives] Electromagnetic Compatibility Directive |
| EV standard | Type 2 3P+N+E 32A 400V~ 22kW | | |
| Rated current | 32A | | |
| Rated voltage | 400V | | |
| Working frequency | 50/60Hz | | |
| Poles | 3P+N+E | | |
| Protection degree IP | IP54 | | |
| Working temperature | -30°C/+50°C | | |
| GLOW WIRE | GW 650°C | | |
| Protection degree IK | IK10 | | |
| Colour | GREY | | |
| Mounting version | SURFACE MOUNTING | | |
| Dimensions | 360x780x264mm | | |