Product Technical Sheet

12 Aug 2021 12:07





204.CA21B-3A3A PILLAR CA 2 SOCKETS WITH LOCK

Type 3A 1P+N+E 16A 230V~ 3,7kW 16A 400V 3P+N+E IP54 IK10

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	LIBERA Series	IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies -
Type of product	PILLAR CA 2 SOCKETS WITH LOCK	applications sites, market	Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations
Synthetical description	PILLAR CA 2 SOCKETS WITH LOCK	EN IEC 61851-1 (2019)	[European Standard] Electric vehicle conductive charging system - Part 1: General requirements
Material	VARNISHED METAL	DIRECTIVE LOW[European Directives] Low VoltageVOLTAGE 2014/35Directive/UEDIRECTIVE EMC[European Directives] Electromagnetic2014/30/UECompatibility Directive	
EV standard	Type 3A 1P+N+E 16A 230V~ 3,7kW		[European Directives] Electromagnetic
Rated current	16A		Compatibility Directive
Rated voltage	400V		
Working frequency	50/60Hz		
Poles	3P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
Protection degree IK	IK10		
Colour	GREY		
Mounting version	ON TURRET		
Dimensions	385x1510x263mm		