Product Technical Sheet

12 Aug 2021 12:09





204.CA22B-T2T2EVPILLAR CA 2 SOCKETS WITH LOCK

Type 2 1P+N+E 32A 230V~ 7,4kW Type 2 3P+N+E 32A 400V~ 22kW 63A 400V 3P+N+E IP54 IK10

Product Approvals

TECHDATA		STANDARDS	AND LAWS
Type of product	PILLAR CA 2 SOCKETS WITH LOCK	IEC 61851-1 (2010)	[International Standard] Electric vehicle conductive charging system - Part 1: General requirements
Commercial series	LIBERA Series	IEC 61439-7 (2018) [International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations DIRECTIVE LOW VOLTAGE 2014/35 Curopean Directives Low Voltage Directive DIRECTIVE EMC [European Directives] Electromagnetic	switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations [European Directives] Low Voltage
Synthetical description	PILLAR CA 2 SOCKETS WITH LOCK		
Material	VARNISHED METAL		
EV standard	Type 2 1P+N+E 32A 230V~ 7,4kW		
EV standard	Type 2 3P+N+E 32A 400V~ 22kW	2014/30/UE	Compatibility Directive
Rated current	63A		
Rated voltage	400V		
Working frequency	50/60Hz		
Poles	3P+N+E		
Protection degree IP	IP54		
Working temperature	-25°C/+40°C		
Protection degree IK	IK10		
Colour	GREY		
Mounting version	ON TURRET		
Dimensions	385x1510x263mm		