## **Product Technical Sheet**

12 Aug 2021 12:10





## 204.CA41E-003 PILLAR CA 4 SOCKETS WITH LOCK

Type 2 1P+N+E 32A 230V~ 7,4kW 63A 400V 3P+N+E IP54 IK10

**Product Approvals** 

| TECHDATA                |                                  | STANDARDS AND LAWS   |  |
|-------------------------|----------------------------------|--|--|
| Commercial series       | LIBERA Series                    | IEC 61439-7 (2018)   | [International Standard] Low-voltage switchgear and controlgear assemblies -   |
| Type of product         | PILLAR CA 4 SOCKETS<br>WITH LOCK | applications such as   | Part 7: Assemblies for specific<br>applications such as marinas, camping<br>sites, market squares, electric vehicle<br>charging stations |
| Synthetical description | PILLAR CA 4 SOCKETS<br>WITH LOCK | EN IEC 61851-1<br>(2019)   | [European Standard] Electric vehicle<br>conductive charging system - Part 1:<br>General requirements                                     |
| Material                | VARNISHED METAL                  | DIRECTIVE LOW[European Directives] Low VoltageVOLTAGE 2014/35Directive/UEDIRECTIVE EMC[European Directives] Electromagnetic2014/30/UECompatibility Directive |  |
| EV standard             | Type 2 1P+N+E 32A 230V~<br>7,4kW |  |  |
| Rated current           | 63A                              |  | Compatibility Directive  |
| Rated voltage           | 400V                             |  |  |
| Working frequency       | 50/60Hz                          |  |  |
| Poles                   | 3P+N+E                           |  |  |
| Protection degree IP    | IP54                             |  |  |
| Working temperature     | -30°C/+50°C                      |  |  |
| Protection degree IK    | IK10                             |  |  |
| Colour                  | GREY                             |  |  |
| Mounting version        | ON TURRET                        |  |  |
| Dimensions              | 385x1510x263mm                   |  |  |