



## 204.CB21B-T2T2EV

# PILLAR CB 2 SOCKETS WITH LOCK

Type 2 1P+N+E 32A 230V~ 7,4kW 32A 400V  
3P+N+E IP54 IK10

Product Approvals

| TECHDATA                |                               | STANDARDS AND LAWS                |  |
|-------------------------|-------------------------------|-----------------------------------|--|
| Commercial series       | LIBERA Series                 | IEC 61439-7 (2018)                | [International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations |
| Type of product         | PILLAR CB 2 SOCKETS WITH LOCK |                                   |  |
| Synthetical description | PILLAR CB 2 SOCKETS WITH LOCK | EN IEC 61851-1 (2019)             | [European Standard] Electric vehicle conductive charging system - Part 1: General requirements   |
| Material                | Al (Stainless steel)          | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive  |
| EV standard             | Type 2 1P+N+E 32A 230V~ 7,4kW | DIRECTIVE EMC 2014/30/UE          | [European Directives] Electromagnetic Compatibility Directive  |
| Rated current           | 32A                           |                                   |  |
| Rated voltage           | 400V                          |                                   |  |
| Working frequency       | 50/60Hz                       |                                   |  |
| Poles                   | 3P+N+E                        |                                   |  |
| Protection degree IP    | IP54                          |                                   |  |
| Working temperature     | -25°C/+40°C                   |                                   |  |
| Protection degree IK    | IK10                          |                                   |  |
| Colour                  | BRUSHED ALLUMINIUM            |                                   |  |
| Mounting version        | ON TURRET                     |                                   |  |
| Dimensions              | 315x1507x250mm                |                                   |  |