## **Product Technical Sheet**

12 Aug 2021 12:13





## 200.23267SBL

## FLUSH-MOUNT. SOCKET WITH LOCK

IP55 32A 3P+N+E 400V BLACK +LED Type 2 3P+N+E 32A 400V~ 22kW

**Product Approvals** 

| TECHDATA                |                                  | STANDARDS AND LAWS   |   |
|-------------------------|----------------------------------|--|---|
| Mounting version        | FLUSH MOUNTING                   | EN 62196-1 (2014) [European Standard] Plugs, socket-outlets and vehicle couplers. Conductive charging of electric vehicles. Part 1: Charging of electric vehicles up to 250 A a.c. and 400 |   |
| Commercial series       | LIBERA Series                    |  |   |
| Type of product         | FLUSH-MOUNT. SOCKET<br>WITH LOCK | EN 62196-2 (2017)  | [European Standard] Plugs, socket-outlets and vehicle couplers. Conductive charging of electric vehicles. Part 2: Dimensional interchangeability requirements for a.c. pin and contact-tube accessories |
| Synthetical description | FLUSH-MOUNT. SOCKET<br>WITH LOCK |  |   |
| Protection degree IP    | IP55                             | DIRECTIVE LOW<br>VOLTAGE 2014/35<br>/UE  | [European Directives] Low Voltage Directive   |
| Rated current           | 32A                              | /UE  |   |
| Poles                   | 3P+N+E                           |  |   |
| Rated voltage           | 400V                             |  |   |
| Colour                  | BLACK                            |  |   |
| Material                | THERMOPLASTIC                    |  |   |
| Notes                   | +LED                             |  |   |
| EV standard             | Type 2 3P+N+E 32A 400V~<br>22kW  |  |   |