



200.23268B

FLUSH-MOUNT. SOCKET WITH LOCK

IP55 32A 3P+N+E 400V BLACK Type 2
3P+N+E 32A 400V~ 22kW

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Mounting version	FLUSH MOUNTING	EN 62196-1 (2014)	[European Standard] Plugs, socket-outlets and vehicle couplers. Conductive charging of electric vehicles. Part 1: Charging of electric vehicles up to 250 A a.c. and 400 A d.c.
Type of product	FLUSH-MOUNT. SOCKET WITH LOCK	EN 62196-2 (2017)	[European Standard] Plugs, socket-outlets and vehicle couplers. Conductive charging of electric vehicles. Part 2: Dimensional interchangeability requirements for a.c. pin and contact-tube accessories
Commercial series	LIBERA Series	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Synthetical description	FLUSH-MOUNT. SOCKET WITH LOCK		
Protection degree IP	IP55		
Rated current	32A		
Poles	3P+N+E		
Rated voltage	400V		
Colour	BLACK		
Material	THERMOPLASTIC		
EV standard	Type 2 3P+N+E 32A 400V~ 22kW		