

## 204.WB11F-T23

### WALL BOX 1 SOCKET TYPE 2

Type 2 1P+N+E 32A 230V~ 7,4kW 32A 230V  
1P+N+E IP54 IK08



Product Approvals

| TECHDATA                |                               | STANDARDS AND LAWS                |  |
|-------------------------|-------------------------------|-----------------------------------|--|
| Commercial series       | LIBERA Series                 | IEC 61439-7 (2018)                | [International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations |
| Type of product         | WALL BOX 1 SOCKET TYPE 2      |                                   |  |
| Synthetical description | WALL BOX 1 SOCKET TYPE 2      | EN IEC 61851-1 (2019)             | [European Standard] Electric vehicle conductive charging system - Part 1: General requirements   |
| Material                | ENGINEERING PLASTIC           | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive  |
| EV standard             | Type 2 1P+N+E 32A 230V~ 7,4kW | DIRECTIVE EMC 2014/30/UE          | [European Directives] Electromagnetic Compatibility Directive  |
| With integrated cable   | Type 2                        |                                   |  |
| Rated current           | 32A                           |                                   |  |
| Rated voltage           | 230V                          |                                   |  |
| Working frequency       | 50/60Hz                       |                                   |  |
| Poles                   | 1P+N+E                        |                                   |  |
| Protection degree IP    | IP54                          |                                   |  |
| Working temperature     | -25°C/+40°C                   |                                   |  |
| GLOW WIRE               | GW 650°C                      |                                   |  |
| Protection degree IK    | IK08                          |                                   |  |
| Colour                  | GREY                          |                                   |  |
| Mounting version        | SURFACE MOUNTING              |                                   |  |
| Dimensions              | 215x350x120mm                 |                                   |  |