



246.12592

FLUSH MOUNTING APPLIANCE INLET

125A 3P+E 9h 200-250V 50Hz 60Hz
114X114MM Screw terminals

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|--------------------------------|-----------------------------------|--|
| Commercial series | OPTIMA Series | CEI EN 60309-1 (1992) | [Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part 1: General requirements |
| Type of product | FLUSH MOUNTING APPLIANCE INLET | CEI EN 60309-2 (1992) | [Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories |
| Synthetical description | FLUSH MOUNTING APPLIANCE INLET | | |
| Mounting version | FLUSH MOUNTING | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Rated current | 125A | | |
| Poles | 3P+E | | |
| Hour position | 9h | | |
| Rated voltage (range) | 200-250V | | |
| Rated voltage | 200-250V | | |
| Working frequency | 60Hz | | |
| Working frequency | 50Hz | | |
| Colour | BLUE | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Watertight | | |
| Protection degree IP | IP66/IP67 | | |
| Protection degree IK | IK08 | | |
| Terminals | Screw terminals | | |
| Contact material | CuZn (brass) | | |

| | |
|----------------------------|---------------|
| Surface treatment contacts | Nickel-plated |
| Flange | 114X114MM |