Product Technical Sheet

12 Aug 2021 12:28





246.12595

FLUSH MOUNTING APPLIANCE INLET

125A 3P+N+E 4h 100-130V 50Hz 60Hz 114X114MM Screw terminals

Product Approvals

TECHDATA		STANDARDS	S AND LAWS
Commercial series	OPTIMA Series	CEI EN 60309-1 (1992)	[Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part
Type of product	FLUSH MOUNTING APPLIANCE INLET	(1992) and couplers for industrial purpos	[Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part
Synthetical description	FLUSH MOUNTING APPLIANCE INLET		2: Dimensional interchangeability requirements for pin and contact-tube accessories
Mounting version	FLUSH MOUNTING	DIRECTIVE LOW [European Directives] Low Voltage VOLTAGE 2014/35 Directive	
Rated current	125A		
Poles	3P+N+E		
Hour position	4h		
Rated voltage (range)	50-200V		
Rated voltage	100-130V		
Working frequency	60Hz		
Working frequency	50Hz		
Colour	YELLOW		
Material	THERMOPLASTIC		
Protection degree	Watertight		
Protection degree IP	IP66/IP67		
Protection degree IK	IK08		
Terminals	Screw terminals		
Contact material	CuZn (brass)		

Surface treatment contacts	Nickel-plated	
Flange	114X114MM	