Product Technical Sheet

12 Aug 2021 12:35





512.M32576SURFACE MOUNTING SOCKET

32A 3P+N+E 7h 480-500V 50Hz 60Hz Screw terminals

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|----------------------------|----------------------------|---|--|
| Type of product | SURFACE MOUNTING SOCKET | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Commercial series | OPTIMA Series | and coup 2: Dimen- requirement | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part |
| Synthetical description | SURFACE MOUNTING SOCKET | | 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Mounting version | SURFACE MOUNTING | DIRECTIVE LOW [European Directives] Low Voltage VOLTAGE 2014/35 Directive /UE | |
| Rated current | 32A | | |
| Poles | 3P+N+E | | |
| Hour position | 7h | | |
| Rated voltage (range) | 400-up | | |
| Rated voltage | 480-500V | | |
| Working frequency | 60Hz | | |
| Working frequency | 50Hz | | |
| Colour | BLACK | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Splash proof | | |
| Protection degree IP | IP44/IP54 | | |
| Protection degree IK | IK08 | | |
| Types of available outlets | ANGLED | | |
| Terminals | Screw terminals | | |

| Contact material | CuZn (brass) | |
|------------------|--------------|--|
| Cable entry | M25X1,5 | |