Product Technical Sheet

12 Aug 2021 12:35





515.125563 SURFACE MOUNTING SOCKET

125A 3P+E 12h TST>50V 50Hz 60Hz Screw terminals

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Type of product	SURFACE MOUNTING SOCKET	CEI EN 60309-1 (1992)	[Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part 1: General requirements
Commercial series	OPTIMA Series	CEI EN 60309-2 [Italian Standard] Plugs, socket-outlets (1992) and couplers for industrial purposes - Part	
Synthetical description	SURFACE MOUNTING SOCKET		2: Dimensional interchangeability requirements for pin and contact-tube accessories
Mounting version	FLUSH/SURFACE MOUNTING	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Rated current	125A		
Poles	3P+E		
Hour position	12h		
Rated voltage (range)	200-250V		
Rated voltage	TST>50V		
Working frequency	60Hz		
Working frequency	50Hz		
Colour	GREY		
Material	THERMOPLASTIC		
Material			
Protection degree	Watertight		
Protection degree IP	IP66/IP67		
Protection degree IK	IK08		

SCAME PARRE S.p.A. Via Costa Erta, 15 24020 Parre (BG) Italy - Tel. 035-705000 Fax 035-703122

Types of available outlets	ANGLED	
Terminals	Screw terminals	
Contact material	CuZn (brass)	
Cable entry	PG 48	
Cable entry		
Cable		
Working temperature		
Lamp holder		