Product Technical Sheet

12 Aug 2021 12:50





415.63663

FLUSH-MOUNTING SOCKET

63A 3P+E 12h TST>50V 50Hz 60Hz 100X110MM Screw terminals

Product Approvals

TECHDATA		STANDARDS	AND LAWS
Commercial series	OPTIMA Series	CEI EN 60309-1 (1992)	[Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part
Type of product	FLUSH-MOUNTING SOCKET	1: General requirements CEI EN 60309-2 [Italian Standard] Plugs, socket-outlets (1992) and couplers for industrial purposes - Pa 2: Dimensional interchangeability requirements for pin and contact-tube accessories	[Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part
Synthetical description	FLUSH-MOUNTING SOCKET		requirements for pin and contact-tube
Mounting version	FLUSH/SURFACE MOUNTING	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Rated current	63A		
Poles	3P+E		
Hour position	12h		
Rated voltage (range)	200-250V		
Rated voltage	TST>50V		
Working frequency	60Hz		
Working frequency	50Hz		
Colour	GREY		
Material	THERMOPLASTIC		
Protection degree	Watertight		
Protection degree IP	IP66/IP67		
Protection degree IK	IK08		
Types of available outlets	ANGLED		

Terminals	Screw terminals	
Contact material	CuZn (brass)	
Flange	100X110MM	