Product Technical Sheet

12 Aug 2021 12:50





415.63677 FLUSH-MOUNTING SOCKET

63A 3P+N+E 5h 600-690V 50Hz 60Hz 100X110MM Screw terminals

Product Approvals

| TECHDATA | | STANDARDS | AND LAWS |
|----------------------------|---------------------------|---|---|
| Commercial series | OPTIMA Series | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part |
| Type of product | FLUSH-MOUNTING SOCKET | EN 60309-2 (1999) | 1: General requirements [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description | FLUSH-MOUNTING SOCKET | | |
| Mounting version | FLUSH/SURFACE MOUNTING | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Rated current | 63A | | |
| Poles | 3P+N+E | | |
| Hour position | 5h | | |
| Rated voltage (range) | 400-up | | |
| Rated voltage | 600-690V | | |
| Working frequency | 60Hz | | |
| Working frequency | 50Hz | | |
| Colour | BLACK | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Watertight | | |
| Protection degree IP | IP66/IP67 | | |
| Protection degree IK | IK08 | | |
| Types of available outlets | ANGLED | | |
| | | | |

| Terminals | Screw terminals |
|------------------|-----------------|
| Contact material | CuZn (brass) |
| Flange | 100X110MM |