Product Technical Sheet

12 Aug 2021 12:51





515.63533

SURFACE MOUNTING SOCKET

63A 2P+E 12h TST>50V 50Hz 60Hz Screw terminals

Product Approvals

| TECHDATA | | STANDARDS | AND LAWS |
|-------------------------|----------------------------|---|--|
| Type of product | SURFACE MOUNTING SOCKET | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Commercial series | OPTIMA Series | EN 60309-2 (1999) [European Standard] Plugs, sociand couplers for industrial purpo 2: Dimensional interchangeability requirements for pin and contact | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part |
| Synthetical description | SURFACE MOUNTING SOCKET | | 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Mounting version | FLUSH/SURFACE MOUNTING | EN 60309-1/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Rated current | 63A | (2007) and coup | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part |
| Poles | 2P+E | | 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Hour position | 12h | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Rated voltage (range) | 200-250V | | |
| Rated voltage | TST>50V | | |
| Working frequency | 60Hz | | |
| Working frequency | 50Hz | | |
| Colour | GREY | | |
| Material | THERMOPLASTIC | | |
| Material | | | |
| Protection degree | Watertight | | |
| Protection degree IP | IP66/IP67 | | |
| Protection degree IK | IK08 | | |
| | | | |

| Types of available outlets | ANGLED | |
|----------------------------|-----------------|--|
| Terminals | Screw terminals | |
| Contact material | CuZn (brass) | |
| Cable entry | PG 29 | |
| Cable entry | | |
| Cable | | |
| Working temperature | | |
| Lamp holder | | |