

# 160.219/C-F MULTI SOCKET

2P+E-10A-(S11) TRANS. TINTED 4x2P+E-10A-(P11)



Product Approvals

| TECHDATA                      |                     | STANDARDS AND LAWS                |  |
|-------------------------------|---------------------|-----------------------------------|--|
| Type of product               | MULTI SOCKET        | CEI 23-50 (2007)                  | [Italian Standard] Prese a spina per usi domestici e similari Parte 1: Prescrizioni generali                                 |
| Commercial series             | BLUELINE Series     | CEI 23-50 V1 (2008)               | [Italian Standard] Prese a spina per usi domestici e similari. Parte 1: Prescrizioni generali                                |
| Synthetical description       | MULTI SOCKET        | CEI 23-50/V2 (2011)               | [Italian Standard] Prese a spina per usi domestici e similari. Parte 1: Prescrizioni generali                                |
| Rated current                 | 10A                 | CEI 23-124 (2012-08)              | [Italian Standard] Spine e prese per usi domestici e similari - Parte 2-7: Prescrizioni particolari per cordoni prolungatori |
| Poles                         | 2P+E                | CEI 23-50 V3 (2015-05)            | [Italian Standard] Prese a spina per usi domestici e similari. Parte 1: Prescrizioni generali                                |
| Rated voltage                 | 250V                | CEI 23-124 V1 (2015-01)           | [Italian Standard] Spine e prese per usi domestici e similari - Parte 2-7: Prescrizioni particolari per cordoni prolungatori |
| Type of plugs                 | 2P+E-10A-(S11)      | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive  |
| Abbreviation of individuation | P11                 | DIRECTIVE RoHS 2011/65/EU         | [European Law] Restriction of the use of certain hazardous substances in electrical and electronic equipment                 |
| No. of available outlets      | 4 NR                |                                   |  |
| Type of sockets               | 4x2P+E-10A-(P11)    |                                   |  |
| Cable length                  | 1,5m                |                                   |  |
| Cable                         | H05VV-F             |                                   |  |
| Cable section                 | 0,75mm <sup>2</sup> |                                   |  |
| Max power                     | MAX 2.300W          |                                   |  |
| Material                      | ENGINEERING PLASTIC |                                   |  |
| Colour                        | TRANS. TINTED       |                                   |  |
| Options                       | With cable and plug |                                   |  |