

Product Technical Sheet

12 Aug 2021 13:19



500.M2421

INTERLOCKED SOCKET

16A 2P 12h 40-50V 50Hz 60Hz
136X125MM_PAR Screw terminals With
electrical interlock

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	OMNIA Series	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Type of product	INTERLOCKED SOCKET	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Synthetical description	INTERLOCKED SOCKET		
Mounting version	SURFACE MOUNTING		
Rated current	16A		
Poles	2P		
Hour position	12h		
Rated voltage (range)	0-50V		
Rated voltage	40-50V		
Working frequency	60Hz		
Working frequency	50Hz		
Colour	WHITE		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP44		
Protection degree IK	IK08		
Terminals	Screw terminals		
Contact material	CuZn (brass)		

Flange	136X125MM_PAR
Options	With electrical interlock
Notes	WITHOUT FUSE HOLDER