

## Product Technical Sheet

12 Aug 2021 13:20



# 566.2421/S

## INTERLOCKED SOCKET

16A 2P 12h 40-50V 106X240MM\_HD Screw terminals With electrical interlock

Product Approvals

| TECHDATA                |                     | STANDARDS AND LAWS   |   |
|-------------------------|---------------------|----------------------|---|
| Type of product         | INTERLOCKED SOCKET  | EN 60309-1 (1999)    | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Commercial series       | ADVANCE 2 HD Series | EN 60309-2 (1999)    | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description | INTERLOCKED SOCKET  |                      |   |
| Mounting version        | SURFACE MOUNTING    |                      |   |
| Rated current           | 16A                 | EN 60309-1/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Poles                   | 2P                  | EN 60309-2/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Hour position           | 12h                 |                      |   |
| Rated voltage (range)   | 0-50V               |                      |   |
| Rated voltage           | 40-50V              |                      |   |
| Colour                  | WHITE               |                      |   |
| Material                | THERMOPLASTIC       |                      |   |
| Protection degree       | Watertight          |                      |   |
| Protection degree IP    | IP66/IP67           |                      |   |
| Protection degree IK    | IK08                |                      |   |
| Terminals               | Screw terminals     |                      |   |
| Contact material        | CuZn (brass)        |                      |   |
| Flange                  | 106X240MM_HD        |                      |   |
| Cable entry             | M25X1,5             |                      |   |

|         |                           |
|---------|---------------------------|
| Options | With electrical interlock |
| Notes   | WITH DIN RAIL (6 MODULES) |
| Padlock | ø5mm                      |