## **Product Technical Sheet**

12 Aug 2021 13:25





## 422.16664

## FLUSH-MOUNTING SOCKET

16A 3P+E 3h 380V 50Hz / 440V 60Hz 50Hz 60Hz 75X75MM Screw terminals

**Product Approvals** 

| TECHDATA                   |                          | STANDARDS                        | AND LAWS  |
|----------------------------|--------------------------|----------------------------------|---|
| Commercial series          | EUREKA Series            | EN 60309-1 (1999)                | [European Standard] Plugs, socket-outlets<br>and couplers for industrial purposes. Part<br>1: General requirements<br>[European Standard] Plugs, socket-outlets<br>and couplers for industrial purposes. Part<br>2: Dimensional interchangeability<br>requirements for pin and contact-tube<br>accessories of harmonized configurations<br>[European Directives] Low Voltage<br>Directive |
| Type of product            | FLUSH-MOUNTING<br>SOCKET | EN 60309-2 (1999)                |   |
| Synthetical description    | FLUSH-MOUNTING<br>SOCKET |                                  |   |
| Mounting version           | FLUSH MOUNTING           | DIRECTIVE LOW<br>VOLTAGE 2014/35 |   |
| Rated current              | 16A                      | /UE                              |   |
| Poles                      | 3P+E                     |                                  |   |
| Hour position              | 3h                       |                                  |   |
| Rated voltage (range)      | 250-400V                 |                                  |   |
| Rated voltage              | 380V 50Hz / 440V 60Hz    |                                  |   |
| Working frequency          | 60Hz                     |                                  |   |
| Working frequency          | 50Hz                     |                                  |   |
| Colour                     | RED                      |                                  |   |
| Material                   | THERMOPLASTIC            |                                  |   |
| Protection degree          | Splash proof             |                                  |   |
| Protection degree IP       | IP44                     |                                  |   |
| Protection degree IK       | IK09                     |                                  |   |
| Types of available outlets | STRAIGHT                 |                                  |   |
| Terminals                  | Screw terminals          |                                  |   |

| Contact material | CuZn (brass) |
|------------------|--------------|
| Flange           | 75X75MM      |