Product Technical Sheet

12 Aug 2021 13:26





422,3264

FLUSH-MOUNTING SOCKET

32A 3P+E 9h 200-250V 50Hz 60Hz 75X75MM Screw terminals

Product Approvals

TECHDATA		STANDARDS	AND LAWS
Commercial series	EUREKA Series	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part
Type of product	FLUSH-MOUNTING SOCKET	and couplers for industrial purposes. I 2: Dimensional interchangeability requirements for pin and contact-tube	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part
Synthetical description	FLUSH-MOUNTING SOCKET		2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Mounting version	FLUSH MOUNTING	DIRECTIVE LOW VOLTAGE 2014/35	[European Directives] Low Voltage Directive
Rated current	32A	/UE	
Poles	3P+E		
Hour position	9h		
Rated voltage (range)	200-250V		
Rated voltage	200-250V		
Working frequency	60Hz		
Working frequency	50Hz		
Colour	BLUE		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP44		
Protection degree IK	IK09		
Types of available outlets	STRAIGHT		
Terminals	Screw terminals		

Contact material	CuZn (brass)	
Flange	75X75MM	