



590.EL4022.SN

SWITCH DISCONNECTOR

40A 1P+SN IP65 82x120x69mm IK09
 GENERAL YELLOW/RED SN (SOLID
 NEUTRAL) GW 650°C

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|---------------------|-----------------------------------|---|
| Commercial series | ISOLATORS-TP Series | EN 60947-3 (2009) | [European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Type of product | SWITCH DISCONNECTOR | EN 60947-1 (2007) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Synthetical description | SWITCH DISCONNECTOR | EN 60947-1/A1 (2011) | [European Standard] Low-voltage switchgear and controlgear - Part 1: General rules |
| Material | ENGINEERING PLASTIC | EN 60947-3/A1 (2012) | [European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Protection degree IP | IP65 | EN 60947-3/A2 (2015) | [European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units |
| Type | GENERAL | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Colour | YELLOW/RED | DIRECTIVE RoHS 2011/65/EU | [European Law] Restriction of the use of certain hazardous substances in electrical and electronic equipment |
| Rated current | 40A | | |
| Poles | 1P+SN | | |
| Dimensions | 82x120x69mm | | |
| Notes | SN (SOLID NEUTRAL) | | |
| GLOW WIRE | GW 650°C | | |
| Protection degree IK | IK09 | | |