Product Technical Sheet

12 Aug 2021 13:43





245.1696/S

SURFACE MOUNT. APPLIANCE INLET

16A 3P+N+E 4h 100-130V 50Hz 60Hz Screw terminals

Product Approvals

TECHDATA		CTANDADDO	AND LAWC
TECHDATA		STANDARDS	
Type of product	SURFACE MOUNT. APPLIANCE INLET	CEI EN 60309-1 (1992)	[Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part 1: General requirements
Commercial series	IEC309 Series	(1992)	[Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part
Synthetical description	SURFACE MOUNT. APPLIANCE INLET		2: Dimensional interchangeability requirements for pin and contact-tube accessories
Mounting version	SURFACE MOUNTING	DIRECTIVE LOW VOLTAGE 2014/35	[European Directives] Low Voltage Directive
Rated current	16A	/UE	
Poles	3P+N+E		
Hour position	4h		
Rated voltage (range)	50-200V		
Rated voltage	100-130V		
Working frequency	50Hz		
Working frequency	60Hz		
Colour	YELLOW		
Material	THERMOPLASTIC		
Protection degree	Watertight		
Protection degree IP	IP67		
Types of available outlets	ANGLED		
Terminals	Screw terminals		
Contact material	CuZn (brass)		

Surface treatment contacts	Nickel-plated	
Cable entry	PG 16	