Product Technical Sheet

12 Aug 2021 13:45





245.6397 SURFACE MOUNT. APPLIANCE INLET

63A 3P+N+E 9h 208-250V 50Hz 60Hz Screw terminals

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	OPTIMA Series	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part
Type of product	SURFACE MOUNT. APPLIANCE INLET	EN 60309-2 (1999) [Euro and 2: Di requ	 General requirements [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Synthetical description	SURFACE MOUNT. APPLIANCE INLET		
Mounting version	SURFACE MOUNTING	DIRECTIVE LOW VOLTAGE 2014/35	[European Directives] Low Voltage Directive
Rated current	63A	/UE	
Poles	3P+N+E		
Hour position	9h		
Rated voltage (range)	200-250V		
Rated voltage	208-250V		
Working frequency	60Hz		
Working frequency	50Hz		
Colour	BLUE		
Material	THERMOPLASTIC		
Protection degree	Watertight		
Protection degree IP	IP66/IP67		
Protection degree IK	IK08		
Types of available outlets	ANGLED		
Terminals	Screw terminals		

Contact material	CuZn (brass)	
Surface treatment contacts	Nickel-plated	
Cable entry	PG 29	