Product Technical Sheet

12 Aug 2021 13:52





527.M3255 SURFACE MOUNTING SOCKET

32A 3P+N+E 9h 208-250V 50Hz 60Hz Screw terminals

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Type of product	SURFACE MOUNTING SOCKET	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Commercial series	OPTIMA Series	EN 60309-2 (1999) [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part	
Synthetical description	SURFACE MOUNTING SOCKET		2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations [European Directives] Low Voltage Directive
Mounting version	SURFACE MOUNTING	DIRECTIVE LOW VOLTAGE 2014/35	
Rated current	32A	/UE	
Poles	3P+N+E		
Hour position	9h		
Rated voltage (range)	200-250V		
Rated voltage	208-250V		
Working frequency	60Hz		
Working frequency	50Hz		
Colour	BLUE		
Material	THERMOPLASTIC		
Protection degree	Watertight		
Protection degree IP	IP66/IP67/IP69		
Protection degree IK	IK08		
Types of available outlets	STRAIGHT		
Terminals	Screw terminals		

SCAME PARRE S.p.A. Via Costa Erta, 15 24020 Parre (BG) Italy - Tel. 035-705000 Fax 035-703122

Contact material	CuZn (brass)
Cable entry	M25X1,5