

## Product Technical Sheet

12 Aug 2021 14:01



# 427.83263

## FLUSH-MOUNTING SOCKET

32A 2P+E 6h 200-250V 50/60Hz 75X75MM  
Screw terminals

Product Approvals

| TECHDATA                   |                       | STANDARDS AND LAWS                |   |
|----------------------------|-----------------------|-----------------------------------|---|
| Commercial series          | EUREKA-MIL Series     | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Type of product            | FLUSH-MOUNTING SOCKET | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description    | FLUSH-MOUNTING SOCKET |                                   |   |
| Mounting version           | FLUSH MOUNTING        | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Rated current              | 32A                   | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Poles                      | 2P+E                  |                                   |   |
| Hour position              | 6h                    |                                   |   |
| Rated voltage (range)      | 200-250V              | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive   |
| Rated voltage              | 200-250V              |                                   |   |
| Working frequency          | 50/60Hz               |                                   |   |
| Colour                     | BLUE                  |                                   |   |
| Material                   | THERMOPLASTIC         |                                   |   |
| Protection degree          | Watertight            |                                   |   |
| Protection degree IP       | IP67                  |                                   |   |
| Protection degree IK       | IK09                  |                                   |   |
| Types of available outlets | STRAIGHT              |                                   |   |
| Terminals                  | Screw terminals       |                                   |   |
| Contact material           | CuZn (brass)          |                                   |   |

Flange

75X75MM