Product Technical Sheet

12 Aug 2021 14:06





544.3270 INTERLOCKED SOCKET

32A 2P+E 4h 100-130V 50Hz 60Hz Screw terminals With mechanical interlock

Product Approvals

No image

TECHDATA		STANDARDS AND LAWS	
Type of product	INTERLOCKED SOCKET	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part
Commercial series	ADVANCE Series	1: General requirementsEN 60309-2 (1999)[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurationsDIRECTIVE LOW VOLTAGE 2014/35[European Directives] Low Voltage Directive	[European Standard] Plugs, socket-outlets
Synthetical description	INTERLOCKED SOCKET		2: Dimensional interchangeability
Mounting version	SURFACE MOUNTING		accessories of harmonized configurations
Rated current	32A		
Poles	2P+E		
Hour position	4h		
Rated voltage (range)	50-200V		
Rated voltage	100-130V		
Working frequency	60Hz		
Working frequency	50Hz		
Colour	YELLOW		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP44		
Protection degree IK	IK07		
Terminals	Screw terminals		
Contact material	CuZn (brass)		

SCAME PARRE S.p.A. Via Costa Erta, 15 24020 Parre (BG) Italy - Tel. 035-705000 Fax 035-703122

Cable entry	PG 21	
Options	With mechanical interlock	
Notes	WITHOUT FUSE HOLDER	