## **Product Technical Sheet**

12 Aug 2021 14:06





## 556.3272 INTERLOCKED SOCKET

32A 3P+E 4h 100-130V 50Hz 60Hz Screw terminals With mechanical interlock

**Product Approvals** 

No image

TECHDATA		STANDARDS	AND LAWS
Type of product	INTERLOCKED SOCKET	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part
Commercial series	ADVANCE Series	and couplers for industrial purpose 2: Dimensional interchangeability requirements for pin and contact-t accessories of harmonized config	[European Standard] Plugs, socket-outlets
Synthetical description	INTERLOCKED SOCKET		2: Dimensional interchangeability
Mounting version	SURFACE MOUNTING		accessories of harmonized configurations [European Directives] Low Voltage
Rated current	32A	VOLTAGE 2014/35 /UE	Directive
Poles	3P+E		
Hour position	4h		
Rated voltage (range)	50-200V		
Rated voltage	100-130V		
Working frequency	60Hz		
Working frequency	50Hz		
Colour	YELLOW		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP66		
Protection degree IK	IK07		
Terminals	Screw terminals		
Contact material	CuZn (brass)		

SCAME PARRE S.p.A. Via Costa Erta, 15 24020 Parre (BG) Italy - Tel. 035-705000 Fax 035-703122

Cable entry	PG 21	
Options	With mechanical interlock	
Notes	WITH FUSE HOLDER	