



558.3278

INTERLOCKED SOCKET

32A 2P+E 9h 380-415V 50Hz 60Hz Screw terminals With mechanical interlock

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|--------------------|-----------------------------------|---|
| Commercial series | ADVANCE HD Series | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Type of product | INTERLOCKED SOCKET | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description | INTERLOCKED SOCKET | | |
| Mounting version | SURFACE MOUNTING | | |
| Rated current | 32A | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Poles | 2P+E | | |
| Hour position | 9h | | |
| Rated voltage (range) | 250-400V | | |
| Rated voltage | 380-415V | | |
| Working frequency | 50Hz | | |
| Working frequency | 60Hz | | |
| Colour | RED | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Splash proof | | |
| Protection degree IP | IP66 | | |
| Terminals | Screw terminals | | |
| Contact material | CuZn (brass) | | |
| Cable entry | PG 21 | | |

| | |
|---------|---------------------------|
| Options | With mechanical interlock |
| Notes | WITH FUSE HOLDER |