Product Technical Sheet

12 Aug 2021 14:11





547.32838

INTERLOCKED SOCKET

32A 2P+E 8h >250V DC Screw terminals With mechanical interlock

Product Approvals

No image

TECHDATA		STANDARDS	AND LAWS
Commercial series	ADVANCE Series	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part
Type of product	INTERLOCKED SOCKET	EN 60309-2 (1999)	1: General requirements [European Standard] Plugs, socket-outlets
Synthetical description	INTERLOCKED SOCKET		and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Mounting version	SURFACE MOUNTING		
Rated current	32A		
Poles	2P+E		
Hour position	8h		
Rated voltage (range)	250-400V		
Rated voltage	>250V		
Working frequency	DC		
Colour	GREY		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP66		
Protection degree IK	IK07		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Cable entry	PG 21		

```
SCAME PARRE S.p.A. Via Costa Erta, 15 24020 Parre (BG) Italy - Tel. 035-705000 Fax 035-703122
```

SCAME PARRE S.p.A. Via Costa Erta, 15 24020 Parre (BG) Italy - Tel. 035-705000 Fax 035-703122

Options Notes

WITHOUT FUSE HOLDER

With mechanical interlock