## **Product Technical Sheet**

12 Aug 2021 14:12





## 547.32876 INTERLOCKED SOCKET

32A 3P+N+E 7h 480-500V 50Hz 60Hz Screw terminals With mechanical interlock

**Product Approvals** 

No image

TECHDATA		STANDARDS AND LAWS	
Type of product	INTERLOCKED SOCKET	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part
Commercial series	ADVANCE Series	1: General requirementsEN 60309-2 (1999)[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurationsDIRECTIVE LOW VOLTAGE 2014/35[European Directives] Low Voltage Directive	[European Standard] Plugs, socket-outlets
Synthetical description	INTERLOCKED SOCKET		2: Dimensional interchangeability
Mounting version	SURFACE MOUNTING		accessories of harmonized configurations
Rated current	32A		
Poles	3P+N+E		
Hour position	7h		
Rated voltage (range)	400-up		
Rated voltage	480-500V		
Working frequency	60Hz		
Working frequency	50Hz		
Colour	BLACK		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP66		
Protection degree IK	IK07		
Terminals	Screw terminals		
Contact material	CuZn (brass)		

SCAME PARRE S.p.A. Via Costa Erta, 15 24020 Parre (BG) Italy - Tel. 035-705000 Fax 035-703122

Cable entry	PG 21
Options	With mechanical interlock
Notes	WITHOUT FUSE HOLDER