



551.32834

INTERLOCKED SOCKET

32A 2P+E 3h >50-250V DC Screw terminals
With mechanical interlock

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|--------------------|-----------------------------------|---|
| Commercial series | ADVANCE Series | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Type of product | INTERLOCKED SOCKET | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description | INTERLOCKED SOCKET | | |
| Mounting version | SURFACE MOUNTING | | |
| Rated current | 32A | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Poles | 2P+E | | |
| Hour position | 3h | | |
| Rated voltage (range) | 50-200V | | |
| Rated voltage | >50-250V | | |
| Working frequency | DC | | |
| Colour | GREY | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Splash proof | | |
| Protection degree IP | IP44 | | |
| Protection degree IK | IK07 | | |
| Terminals | Screw terminals | | |
| Contact material | CuZn (brass) | | |
| Cable entry | PG 21 | | |

| | |
|---------|---------------------------|
| Options | With mechanical interlock |
| Notes | WITH FUSE HOLDER |