Product Technical Sheet

12 Aug 2021 14:12





551.32877 INTERLOCKED SOCKET

32A 3P+N+E 5h 600-690V 50Hz 60Hz Screw terminals With mechanical interlock

Product Approvals

No image

TECHDATA		STANDARDS	AND LAWS
Type of product	INTERLOCKED SOCKET	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part
Commercial series	ADVANCE Series	EN 60309-2 (1999) [European Stat and couplers for 2: Dimensional	1: General requirements [European Standard] Plugs, socket-outlets
Synthetical description	INTERLOCKED SOCKET		and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube
Mounting version	SURFACE MOUNTING	DIRECTIVE LOW [European Directives] Low Voltage VOLTAGE 2014/35 Directive	accessories of harmonized configurations
Rated current	32A		
Poles	3P+N+E		
Hour position	5h		
Rated voltage (range)	400-up		
Rated voltage	600-690V		
Working frequency	60Hz		
Working frequency	50Hz		
Colour	BLACK		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP44		
Protection degree IK	IK07		
Terminals	Screw terminals		
Contact material	CuZn (brass)		

SCAME PARRE S.p.A. Via Costa Erta, 15 24020 Parre (BG) Italy - Tel. 035-705000 Fax 035-703122

Cable entry	PG 21	
Options	With mechanical interlock	
Notes	WITH FUSE HOLDER	