



556.32875

INTERLOCKED SOCKET

32A 3P+N+E 11h 440-460V 60Hz Screw terminals With mechanical interlock

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Type of product	INTERLOCKED SOCKET	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Commercial series	ADVANCE Series	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Synthetical description	INTERLOCKED SOCKET		
Mounting version	SURFACE MOUNTING		
Rated current	32A	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Poles	3P+N+E		
Hour position	11h		
Rated voltage (range)	400-up		
Rated voltage	440-460V		
Working frequency	60Hz		
Colour	RED		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP66		
Protection degree IK	IK07		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Cable entry	PG 21		

Options	With mechanical interlock
Notes	WITH FUSE HOLDER