## **Product Technical Sheet**

12 Aug 2021 14:14





## 557.32833

## INTERLOCKED SOCKET

32A 2P+E 12h TST>50V 50Hz 60Hz Screw terminals With mechanical interlock

**Product Approvals** 

No image

TECHDATA		STANDARDS	AND LAWS
Type of product	INTERLOCKED SOCKET	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part
Commercial series	ADVANCE Series	EN 60309-2 (1999)	1: General requirements [European Standard] Plugs, socket-outlets
Synthetical description	INTERLOCKED SOCKET		and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube
Mounting version	SURFACE MOUNTING	DIRECTIVE LOW	accessories of harmonized configurations [European Directives] Low Voltage
Rated current	32A	VOLTAGE 2014/35	Directive
Poles	2P+E		
Hour position	12h		
Rated voltage (range)	200-250V		
Rated voltage	TST>50V		
Working frequency	50Hz		
Working frequency	60Hz		
Colour	GREY		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP66		
Protection degree IK	IK07		
Terminals	Screw terminals		
Contact material	CuZn (brass)		

SCAME PARRE S.p.A. Via Costa Erta, 15 24020 Parre (BG) Italy - Tel. 035-705000 Fax 035-703122

OptionsWith mechanical interlockNotesWITH DIN RAIL (4 MODULES)	Cable entry	PG 21	
	Options	With mechanical interlock	
	Notes		