



590.EFQL332

FIXED GUARD AUTOMATIC CUT-OUT

32A 3P II 2GD

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Type of product	FIXED GUARD AUTOMATIC CUT-OUT	EN 60079-0 (2006)	[European Standard] Electrical apparatus for explosive gas atmospheres. General requirements
Commercial series	ISOX	EN 61241-0 (2006)	[European Standard] Electrical apparatus for use in the presence of combustible dust. General requirements
Synthetical description	FIXED GUARD AUTOMATIC CUT-OUT	EN 61241-1 (2004)	[European Standard] Electrical apparatus for use in the presence of combustible dust. Protection by enclosures "tD"
Material	METAL	IEC 60079-0 (2004-01)	[International Standard] Electrical Apparatus for Explosive Gas Atmospheres - Part 0: General Requirements.
Rated current	32A	IEC 60079-1 (2003-11)	[International Standard] Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d".
Poles	3P	IEC 61241-0 (2004-07)	[International Standard] Electrical apparatus for use in the presence of combustible dust - Part 0: General requirements
Rated voltage	380-415V	IEC 61241-1 (2004-05)	[International Standard] Electrical apparatus for use in the presence of combustible dust - Part 1: Protection by enclosures 'tD'
Group and categories EX	II 2GD	EN 60079-1 (2004)	[European Standard] Electrical apparatus for explosive gas atmospheres - Part 1: Flameproof enclosures 'd'
Ambient temperature Ta min	-30 °C	DIRECTIVE ATEX 2014/34/UE	[European Directives] Atmosphere Explosive
Ambient temperature Ta max	55 °C		