Product Technical Sheet

12 Aug 2021 14:34





559.6374

INTERLOCKED SOCKET

63A 3P+E 9h 200-250V 50Hz 60Hz Screw terminals With mechanical interlock

Product Approvals

No image

TECHDATA	STANDARDS AND LAWS		
Commercial series	ADVANCE HD Series	EN 60309-1 (1999)	and couplers for industrial purposes. Part 1: General requirements [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations [European Directives] Low Voltage
Type of product	INTERLOCKED SOCKET	EN 60309-2 (1999)	
Synthetical description	INTERLOCKED SOCKET		
Mounting version	SURFACE MOUNTING	DIRECTIVE LOW	
Rated current	63A	VOLTAGE 2014/35 /UE	
Poles	3P+E		
Hour position	9h		
Rated voltage (range)	200-250V		
Rated voltage	200-250V		
Working frequency	50Hz		
Working frequency	60Hz		
Colour	BLUE		
Material	THERMOPLASTIC		
Protection degree	Splash proof		
Protection degree IP	IP66		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Cable entry	PG 29		

SCAME PARRE S.p.A. Via Costa Erta, 15 24020 Parre (BG) Italy - Tel. 035-705000 Fax 035-703122

Options	With mechanical interlock
Notes	WITH DIN RAIL (4 MODULES)