



563.16837

INTERLOCKED SOCKET

16A 2P+E 5h 277V 60Hz 106X240MM Screw terminals With mechanical interlock

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	ADVANCE 2 Series	CEI EN 60309-1 (1992)	[Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part 1: General requirements
Type of product	INTERLOCKED SOCKET	CEI EN 60309-2 (1992)	[Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories
Synthetical description	INTERLOCKED SOCKET		
Mounting version	SURFACE MOUNTING		
Rated current	16A	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Poles	2P+E		
Hour position	5h		
Rated voltage (range)	250-400V		
Rated voltage	277V		
Working frequency	60Hz		
Colour	GREY		
Material	THERMOPLASTIC		
Protection degree	Watertight		
Protection degree IP	IP66/IP67		
Protection degree IK	IK07		
Terminals	Screw terminals		
Contact material	CuZn (brass)		
Flange	106X240MM		

Cable entry	M25X1,5
Options	With mechanical interlock
Notes	WITH FUSE HOLDER
Padlock	ø5mm