



# 564.6379

## INTERLOCKED SOCKET

63A 3P+N+E 4h 100-130V 50Hz 60Hz  
136X390MM\_HD Screw terminals With  
mechanical interlock

Product Approvals

| TECHDATA                |                     | STANDARDS AND LAWS                |   |
|-------------------------|---------------------|-----------------------------------|---|
| Commercial series       | ADVANCE 2 HD Series | EN 60309-1 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Type of product         | INTERLOCKED SOCKET  | EN 60309-2 (1999)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Synthetical description | INTERLOCKED SOCKET  |                                   |   |
| Mounting version        | SURFACE MOUNTING    |                                   |   |
| Rated current           | 63A                 | EN 60309-1/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Poles                   | 3P+N+E              | EN 60309-2/A1 (2007)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Hour position           | 4h                  |                                   |   |
| Rated voltage (range)   | 50-200V             | EN 60309-4 (2007)                 | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock   |
| Rated voltage           | 100-130V            |                                   |   |
| Working frequency       | 60Hz                | EN 60309-1/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements  |
| Working frequency       | 50Hz                | EN 60309-2/A2 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Colour                  | YELLOW              |                                   |   |
| Material                | THERMOPLASTIC       |                                   |   |
| Protection degree       | Watertight          | EN 60309-4/A1 (2012)              | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock   |
| Protection degree IP    | IP66/IP67           |                                   |   |
| Protection degree IK    | IK08                | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive   |
| Terminals               | Screw terminals     |                                   |   |
| Contact material        | CuZn (brass)        |                                   |   |

|             |                           |
|-------------|---------------------------|
| Flange      | 136X390MM_HD              |
| Cable entry | DRILLING POINT MARK       |
| Options     | With mechanical interlock |
| Notes       | WITH FUSE HOLDER          |
| Padlock     | ø5mm                      |