



567.16837

INTERLOCKED SOCKET

16A 2P+E 5h 277V 60Hz 136X390MM Screw terminals With mechanical interlock

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|-------------------------|--------------------|-----------------------------------|--|
| Type of product | INTERLOCKED SOCKET | CEI EN 60309-1 (1992) | [Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part 1: General requirements |
| Commercial series | ADVANCE 2 Series | CEI EN 60309-2 (1992) | [Italian Standard] Plugs, socket-outlets and couplers for industrial purposes - Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories |
| Synthetical description | INTERLOCKED SOCKET | | |
| Mounting version | SURFACE MOUNTING | | |
| Rated current | 16A | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Poles | 2P+E | | |
| Hour position | 5h | | |
| Rated voltage (range) | 250-400V | | |
| Rated voltage | 277V | | |
| Working frequency | 60Hz | | |
| Colour | GREY | | |
| Material | THERMOPLASTIC | | |
| Protection degree | Splash proof | | |
| Protection degree IP | IP44 | | |
| Protection degree IK | IK07 | | |
| Terminals | Screw terminals | | |
| Contact material | CuZn (brass) | | |
| Flange | 136X390MM | | |

| | |
|-------------|---------------------------|
| Cable entry | DRILLING POINT MARK |
| Options | With mechanical interlock |
| Notes | WITH DIN RAIL (6 MODULES) |
| Padlock | ø5mm |